

SECTION 096800 - CARPETING

PART 1 - GENERAL

1.1 SECTION REQUIREMENTS

- A. Submittals: Product Data.
- B. Comply with CRI 104, Section 6, "Site Conditions."
- C. Extra Materials: Deliver to Owner full-width carpet equal to 5 percent of each type and color carpet installed, packaged with protective covering for storage.

PART 2 - PRODUCTS

2.1 AVAILABLE PRODUCTS:

- A. CARPET F-1, Carpet Color 1:
  - 1. Gibraltar Commercial Carpets "North Peak".
    - a. Color and Pattern: Indicated.
  - 2. Dye Method: Solution
  - 3. Face Weight: 28 Ounces per square yard excluding weight of backings.
  - 4. Primary Backing: Unknown.
  - 5. Secondary Backing: N/A.
  - 6. Pile Height: -
  - 7. Primary Fiber: Nylon 100%.
- B. CARPET F-2, Carpet Color 2:
  - 1. Britlin, Incorporated "Endurance".
    - a. Color and Pattern: Indicated.
  - 2. Dye Method: Solution
  - 3. Weight: 50 Ounces per square yard..
  - 4. Primary Backing: All weather non-skid rubber.
  - 5. Primary Fiber: Olefin 100%.

6. Pile Height: .4”.

### PART 3 - EXECUTION

#### 3.1 INSTALLATION

- A. Comply with CRI 104, Section 8, "Direct Glue-Down" and Section 9, "Double Glue-Down". Provide double glue down installation at rooms indicated to receive carpet cushion.
- B. Maintain uniformity of carpet direction and lay of pile. At doorways, center seams under door in closed position. Bind or seal cut edges as recommended by carpet manufacturer.
- C. Install pattern parallel to walls and borders.

END OF SECTION 096800